






# HP DEMI DOUBLE

DEMI DOUBLE can be used for cleaning all surfaces with an extraordinary NO SPOTS effect. After using the softener, surface drying is no longer necessary. These systems protect all pipes, feed pumps, boilers, showers, taps and ice makers from impurities, corrosion and limescale deposits. The system is designed for softening, for a complete or partial removal of the total hardness and for the prevention of limescale deposits. DEMI DOUBLE uses special high ion exchange resins, and are able to reach flow rates of 400 liters / hour per liter of resin. Conventional softeners reach flow rates of only 40-60 liters per hour per liter of resin. The DEMI DOUBLE softeners, despite having higher flow rates than conventional softeners 5 times larger, use 50 to 70% less water and salt during regeneration. For example, a crew of (4-6 people) with a consumption of 200 m<sup>3</sup> / year of water at 30 ° F hardness, will have an annual consumption of only 100-105 kg of salt per year. The system works without electricity and is fully automatic.



**DEMI DOUBLE**



Model	
HP Demi Double	
25 Kg salt bag	
Technical specs.	
Max pressure bar	6
Min pressure bar	2
Max pressure °C 50	50
Total weight Kg	30
Dimensions mm (WxHxD)	480 x 400 x 570



Since 1995 at the service of the water industry



Registered to:  
ISO 9001  
ISO 14001  
OHSAS 18001

