

HP SC DOUBLE series is supplied in a unique vertical frame, containing two independent machines. They can be used in singular or twin mode depending on the water request and allow a continuous production even in case of maintenance of one of the two units (half of the total flow rate is guaranteed). Available in the AUTO, RP TRONIC and with the following voltages: 110VAC 60Hz - 230VAC 50Hz - 230VAC 60Hz - 380VAC 50Hz - 440VAC 60Hz. MODBUS protocol standard installed on all the units. Compatible with BiBi and Part-NET Interface.



Touch screen 7" remote control panel

HP SCD V 660-6

Model	Lt/h	Membranes
HP SCDV 400	400	6-2540
HP SCDV 540/4	540	4-31540
HP SCDV 660/6	660	6-31540
HP SCDV 880/8	880	8-31540

Optional accessories	
Extra for RP TRONIC Version (Automatic Pressure Regulation)	+3 years warranty
Extra for Part-NET Interface (compatibile with: Garmin, Raymarine, Furuno and Navico)	
Extra for BiBi internet remote control system	+1 year warranty
Extra for Automatic Membranes Conserving System (AMCS)	

MODEL	SCDV 400	SCDV 540/4	SCDV 660/6	SCDV 880/8
Flow rate Lt/h	400	540	660	880
Nominal flow rate Lt/h	498	664	840	1120
Daily flow rate Lt/day	9600	12960	15840	21120
Nominal flow rate Lt/day	11952	15936	20160	26880
Installed Power kW	2X2,2	2X2,2	2X3	2X3
Total Weight Kg	202	153	175	197
Overall dimensions mm WxHxD	840 X 1100 X 495			

Flow rates are calculated for sea waters with the following characteristics: 35000 ppm a 25°C at 60 bar.  
20% Price increase for 60Hz and 230V triphase models.